Configuration File Overview

Setting	Default Value	Description
AD_Max_Age	45 (days)	For Active Directory discovery, only include devices that have logged in within the last N number of days.
Max_Threads	15 (threads)	The maximum number of computers that AIT will inventory concurrently.
Scan_Frequency	10080 (minutes)	How long (in minutes) before AIT will re-scan a device that has already been scanned. The default is 7 days.
Export_Last_Seen_Days	90 (days)	Devices that have not been sucessfully scanned within the last seen days are excluded from the exports.
LogToScreenLevel	3	The logging level that is output to the screen. 1. Critical 2. Warning 3. Information 4. Verbose
Scan_Timeout	600 (seconds)	How long to wait (in seconds) for a device to be scanned before timing out and aborting the scan. The default is 10 minutes.
DataStorePath	Default	 The path to the data store. Default signifies the default location, which is either: C:\ProgramData\Autodesk\AIT if in Program Files Same folder as AIT.exe if not in Program Files Alternatively, a UNC path can be specified. Only used for logon/startup script or 3rd party tool deployment, for example: \\SERVER01\AIT\Data\

Setting	Default Value	Description
PerComputerDataStore	False	If True , each inventoried computer running AIT will output a separate data store with the name of the computer. Only used for logon/startup script or 3rd party tool deployment. If False , results are output to the default DataStore.xml.
Force_WMI_Instrumentation	True	Force the use of Windows Management Instrumentation rather than auto-detecting if Windows Management Infrastructure is available.